JINGTONG 精通®

JT-A7

CLEAR AUDIO
COPY FREQUENCY
SHORTCUT



- Monitor/Square function
- Scan/VOX
- (TOT) Time out timer
- (BCL) Busy channel lockout
- Battery save
- Low battery alarm/ Channel announcement

www.jtdjj.com
因为专业 所以精通

福建泉州市精通电子有限公司
JINGTONG (QUANZHOU) ELECTRONICS CO.LTD.

JINGTONG 精通®

JT-A7
Business Walkie Talkie

Main Function

- Monitor/Square function
- Scan
- (VOX)
- (TOT) Time out timer
- (BCL) Busy channel lockout
- Battery save
- Low battery alarm
- Channel announcement

Basic parameters

BRIEF PARAMETER	
Frequency range	400-450MHz
Operating temperature range	-20°C-50°C
Channel capacity	16channels
Communication system	Simplex or Double frequency simplex
Weight	268g(including battery pack)
Battery capacity	1600mAh
Output power	2watts
Modulation Type	FM(F3E)
Frequency deviation	≤±5KHz
Spurious Emission	<-60dB
TX current	≤1.5A
Frequency stability	±2.5ppm
RX sensitivity	<0.18μ V
Audio sensitivity	≥400MW
Standby current	72mA(36 mA Power save conditian:36mA)
Dimension	101(L)X52(W)X35(D)mm

Standard Accessories



Radio device*1 | Belt clip*1 | Antenna*1 | Battery*1 | Adaptor & cable*1 | Lanyard*1

www.jtdjj.com
因为专业 所以精通

福建泉州市精通电子有限公司
JINGTONG (QUANZHOU) ELECTRONICS CO.LTD.

Authorized distributor